

DALAPRO[®]

ROLL HYDRO

Ready-mixed filler for roller application in wet rooms.



A blue tinted roll filler for wetrooms.

Provides a hard and water repellent surface.

Suitable for use in areas that requires a hard and durable surface.

Roll application makes smoothing fast and easy. And the work is more ergonomic correct.

On plasterboard and concrete.

Approved for embedding paper tape.

For new construction and renovation.

DALAPRO[®] ROLL HYDRO

Ready-mixed filler for roller application in wet rooms.

PRODUCT INFORMATION

Dalapro Roll Hydro is a blue ready-mixed filler for roller application in wet rooms or where an extra-durable surface is desired on all common types of indoor wall and ceiling surfaces. A high binder content in the filler gives the product a hard, water-repellent surface, and maximum adhesion to the substrate. The smooth consistency means that the filler can be spread evenly over the entire surface without effort. Apart from saving time, roller application of filler is ergonomic, causing less strain on the body. The product is suitable for joint filling and thin smoothing.

USE

Suitable for embedding paper tape. Combined with Certain-Teed Marco Joint Tape, the product is suitable for joint filling on plasterboard. Meets CE-marking requirements in accordance with EN 13963. Manufactured in accordance with ISO 9001 and ISO 14001. When finishing plasterboard: follow recommendations in accordance with EN 13963 or National guidelines for finishing plasterboards.

INSTRUCTIONS

For roller application on clean, dry and firmly attached surfaces at a minimum temperature of +5°C. The filled surface is sanded when it has dried. Use sandpaper with particle size 100-120. Eye protection and a dust mask are recommended when sanding. Dust off before the next treatment. Filled surfaces should be primed before wallpapering.

MATERIAL CONSUMPTION

Joint filling on plasterboard = approx. 0.3 l/m.
For thin smoothing with a 1 mm layer thickness:
approximately 1 litre/square metre.

CLEANING AND DISPOSAL

Remove as much filler as possible from the tools before cleaning them in water. Filler residues must not be poured down the drain, but taken to the local waste disposal centre. Empty packaging completely and recycle it.

STORAGE

Filler has a limited shelf life and is date-marked. Unopened packaging can be kept in a dark place, free from frost, for up to 12 months. Containers that have been opened must be sealed well.

Visit dalapro.com for more information.

TECHNICAL DATA

Binder: Latex co-polymer

Solvent: Water

Filler: Microspheres and white dolomite

Particle size: Max 0,2 mm

pH: Approx. 9

Colour: Blue

Flammability: Does not spread or support fire

Packaging: 12 litre plastic bucket



Dalapro Roll Hydro is packaged in a bucket manufactured mostly of recycled plastic.



This product data sheet is provided for guidance only. The data presented does not constitute a guarantee that the product has certain properties or is suitable for a particular area of application. These values apply under normal circumstances. We reserve the right to make changes without prior notice. Users are responsible for ensuring they use the latest edition of this data sheet. Checks can be made at www.dalapro.com

Last amended 05/10/2023

Saint-Gobain Sweden AB, Scanspac
Kemivägen 7
SE-705 97 Glanshammar
+46 (0)19-46 34 00
dalapro.com
info@dalapro.com